


Key Features

- ❖ 50/60 fps at 1080P
- ❖ Auto back focus(ABF)
- ❖ Smart Detection supported
- ❖ Wide Dynamic Range (120dB)
- ❖ 1/2.8" 2Megapixel scan CMOS
- ❖ Efficient light sensitivity feature
- ❖ Effective protection against lightning
- ❖ H.264, H.265 encoding (Triple-Stream)
- ❖ Optimized H.265 codec implementation
- ❖ PoE, PoC power supply technology support
- ❖ Intelligent Video System for scene analytics
- ❖ 120dB wide dynamic range, ICR (Day/Night)
- ❖ 2/1 Alarm in/out, 1/1 audio in/out(Built-in Mic)



Technical Specifications

Model	SCM-FBX02VF-WD32FE
Product Name	2.0 Megapixel WDR, IP Box Network Camera
Camera	
Image Sensor	1/2.8" 2Megapixel scan CMOS
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	Auto/Manual
Mini. Illumination	0.004 Lux, 0.002Lux
Signal Noise Ratio	More than 50dB
Lens Mount Type	C/CS
Video	
Video Compression	H.265+/H.265/H.264+/H.264

Securicorp Technologies UK Ltd., All Rights Reserved. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to product. Securicorp Technologies UK Ltd. may make changes and description without notice.



Video Bit Rate	H.264: 24~9472Kbps H.265: 14~5632Kbps
Resolution	1080P(1920x1080)/ 720P(1280x720)/ VGA(640x480)
Frame Rate	First stream: 50/60 fps - 1080 P Second stream: 50/60 fps - D1 Third stream: 25/30 fps - 1080 P
Intelligent Function	Face Detection
Day/Night	Auto (ICR), Color, B/W
Noise Reduction	3D DNR
Audio	
Audio Compression	G.726/ G.711a/ G.711Mu /AAC
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Protocol	HTTP; HTTPs; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Interoperability	PSIA, CGI, ONVIF
Max User Access	10 Users /20 Users
Smart Phone	IOS, Android
Browser	IE, Chrome, Firefox, Safari
Interface	
Video	1 port(BNC,1Vp-p,75Ω)
Audio	1/1 channel In/Out, 1 Built -in Mic
RS485	1 port
Environmental	
Power Consumption	<8W
Storage Environment	-30° C ~ +60° C (-22° F ~ +140° F) / RH < 95%
Operating Environment	-30° C ~ +60° C (-22° F ~ +140° F) / RH < 95%
Dimensions (cm)	13.54cm×7.44cm×6.55cm
Weight (g)	660g

Securicorp Technologies UK Ltd., All Rights Reserved. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to product. Securicorp Technologies UK Ltd. may make changes and description without notice.

